



(19)

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 792 819 B1

(12)

## EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention  
of the grant of the patent:  
21.04.1999 Bulletin 1999/16

(51) Int. Cl.<sup>6</sup>: B65D 71/50

(21) Application number: 97300899.8

(22) Date of filing: 12.02.1997

### (54) Carrier device and package

Träger und Packung

Dispositif de portage et emballage

(84) Designated Contracting States:  
AT BE CH DE DK ES FI FR GB GR IE IT LI LU NL  
PT SE

(30) Priority: 28.02.1996 US 608522

(43) Date of publication of application:  
03.09.1997 Bulletin 1997/36

(73) Proprietor:  
ILLINOIS TOOL WORKS INC.  
Glenview, Illinois 60025 (US)

(72) Inventors:

- Marco, Leslie  
Bloomington, Illinois (US)
- Olsen, Robert  
Medinah, Illinois (US)

(74) Representative:

Rackham, Stephen Neil  
GILL JENNINGS & EVERY,  
Broadgate House,  
7 Eldon Street  
London EC2M 7LH (GB)

(56) References cited:

EP-A- 0 728 674

US-A- 5 174 441

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 792 819 B1

## Descripti n

[0001] This invention is generally directed to a carrier device which is used to secure containers together to form a package which allows for the quick and easy removal of the containers.

[0002] Currently, several types of carrier devices can be found in the art for securing containers together into a package. Some of these carrier device provide quick release structure for allowing a consumer to quickly and easily release the containers from the carrier device.

[0003] One such carrier device can be found in United States Patent No. 3,038,602 which discloses a container carrier device that holds six cans in a package array. The carrier device is positioned near the top of each can. A zipper strip is provided on the carrier device and is positioned between the rows of cans. A consumer releases the cans from the carrier device by tearing the zipper strip. When the zipper strip is torn, the carrier device creates two sets of packages, each consisting of three cans.

[0004] One problem which arises with this type of quick release carrier device is that when the zipper strip is torn, two separate packages are formed which may be undesirable for handling the cans.

[0005] Another such carrier device can be found in United States Patent No. 5,174,441, a state of the art corresponding to the preamble of claim 1, which discloses a tear-open container carrier device that holds a plurality of cans in a package. Each can is held within a container encircling band. Zip strips are provided on the carrier device exterior to the container encircling bands. A consumer releases the cans from the carrier device by tearing the zip strips. The removal of the strip ruptures each individual band.

[0006] The present invention presents a novel quick release structure or zip strip for a carrier device which allows the containers to be released from the carrier device one at a time or in succession.

[0007] According to this invention a carrier device for carrying a plurality of containers comprising at least one container engaging portion formed from a flexible material, said container engaging portion comprising bands disposed in a row and defining apertures therein, each said aperture for holding a single container therein, said bands having an outer margin portion extending longitudinally of said row, and separating means on said outer margin portion, is characterised in that said separating means comprises a perforation line associated with each said aperture and an elongated slit between adjacent perforation lines, each said perforation line directing tearing forces into the respective apertures, for separating a portion of said outer margin portion from the remainder of said outer margin portion, said separable outer margin portion defining a zip strip, said tearing forces being formed by pulling said zip strip to separate said zip strip from the remainder of the outer margin portion.

[0008] In one embodiment a first perforation line starts at a side margin of the carrier device and extends inwardly therefrom and substantially to the first aperture. A first slit is generally aligned with a portion of the perforation line and is separated from the perforation line by a narrow web of carrier device material. One of the openings is substantially aligned with the slit and separated therefrom by a narrow web of carrier device material.

[0009] A second perforation line starts on the opposite side of the opening and extends across the outer margin of the carrier device and substantially to the middle aperture. A second slit is substantially aligned with a portion of the second perforation line and is separated from the second perforation line by a narrow web of carrier device material. The other of the openings is substantially aligned with the second slit and separated therefrom by a narrow web of carrier device material.

[0010] Finally, a third perforation line starts on the opposite side of the second opening and extends across the outer margin of the carrier device and substantially to the third aperture.

[0011] It is to be noted that as shown and described herein, the carrier device has three apertures. The present invention is not intended to be so limited and the carrier device can be formed to include two or more apertures in accordance with the present invention.

[0012] Each zip strip can be torn along the first perforation line to direct the tearing forces inwardly to the first aperture in order to release the container held therein. The narrow web of carrier device material between the perforation line and the opening is ruptured as the zip strip is pulled. The zip strip separates itself from the remainder of the carrier device along the slit and thereafter, the narrow web of material between the opening and the second perforation line can be selectively ruptured to release the container in the middle aperture.

[0013] Thereafter, the same process is repeated for releasing the subsequent containers from the carrier device.

[0014] It should be understood that the openings between the slits and subsequent perforation line could be eliminated and the subsequent perforation line could be directly interconnected to the prior adjacent slit.

[0015] A particular example of a carrier and package in accordance with this invention will now be described with reference to the accompanying drawings, wherein like reference numerals identify like elements; and in which:

Figure 1 is a side elevational view of a carrier device having zip strips;

Figure 2 is a perspective view of the carrier device shown in Figure 1 shown surrounding a plurality of containers with the zip strip being partially torn;

Figure 2a is a partial, enlarged perspective view of the carrier device shown in Figure 2 showing the zip

strip being partially torn; and,

Figure 3 is a perspective view of the carrier device shown in Figure 1 shown surrounding a plurality of containers with the zip strip fully torn to release all of the containers therefrom.

[0016] As shown in the drawings, a multi-packaging device or carrier device 20, constructed according to the teachings of the present invention, is used to hold a plurality of containers 22. The carrier device 20 includes at least one novel zip strip 24 which can be pulled to easily and quickly release the containers 22 held within the carrier device 20. The zip strip 24 can be pulled so as to release the containers 22 one at a time or to release all of the containers 22 in rapid succession.

[0017] As shown in Figure 2, the carrier device 20 is used to carry six bottles 22 to form a package 26. It is to be understood that other types of containers can be carried by the carrier device 20, such as cans or the like.

[0018] A preferred embodiment of the general structure of the carrier device 20 and the method for forming the same is disclosed in EP-A-0678456. The carrier device is made of a suitable flexible, resilient, stretchable material, such as plastic. Preferably, the carrier device 20 is made of a low density polyethylene so that the carrier device 20 can be stretched over the containers 22 and conform to side walls 28 of the containers 22. The carrier device 20 may be applied to the containers 22 by known means, for example, by the machines disclosed in United States Patent Nos. 4,250,682 or 3,204,386.

[0019] When the containers 22 are secured in a package arrangement by the carrier device 20, the containers 22 are aligned in an array so to form two rows. As shown, each row has three bottles. It is to be understood that the carrier device 20 operates equally well with any number of containers.

[0020] The carrier device 20 includes container engaging portions 30, 32, each formed from a plurality of annular rings or bands 34. Each band 34 has an inner margin 36, an outer margin 38 and side margins 40, 42 which connect the inner margin 36 of each band 34 to the outer margin 38 of the same band 34. The side margins of adjacent bands 34 are integrally joined together so that the outer margins 38 of the bands 34 are continuous and uninterrupted along the length of the carrier device 20.

[0021] The bands 34 are connected or joined together by a seam or a joined portion 44 along the inner margins 36 of each band 34. The annular bands 34 define a plurality of shaped apertures 46a, 46b, 46c for securely holding the margin of each aperture 46a, 46b, 46c is slightly contoured.

[0022] The container engaging portions 30, 32 freely extend from the joined portion 44. The joined portion 44 is generally planar with the plane of the container engaging portions 30, 32 when the carrier device 20 is not assembled with containers 22 and projects gener-

ally perpendicular to the plane of the container engaging portions 30, 32 when the carrier device 20 is assembled with the containers 22.

[0023] The joined portion 44 is formed by extruding a strip or layer of resilient, stretchable material, such as plastic, preferably low density polyethylene material, between the inner margins 36 of each annular band 34 and thereafter sufficiently melting and merging the inner margins 36 of the container engaging portions 22, 24 and the layer of extruded plastic together by known means, preferably by heat sealing and fusing the layers together, to form a strong, integral bond. The joined portion 44 may be partially interrupted along its length by cutouts.

[0024] The carrier device 20 includes a handle portion 48 which extends upwardly from the joined portion 44 of the carrier device 20. The handle portion 48 includes two sides portions which are formed from the two sheets that are used to form the carrier device 20. A bond (not shown), formed by heat sealing or by extruding a layer of plastic material between the side portion, may be provided along an upper portion of the handle portion 48 to prevent the side portions of the handle portion 48 from separating thereby making the handle portion 48 easy to grasp by a consumer. Alternatively, the carrier device 20 can be constructed without a handle portion 48.

[0025] The zip strip 24 on each container engaging portion 30, 32 is positioned along the outer margin 38 of each container engaging portion 30, 32 for releasing containers 22 from the carrier device 20 one at a time while maintaining the remainder of the containers 22 in the package 26, or for releasing the containers 22 in each row from the carrier device 20 in rapid succession. The zip strip 24 is used to completely rupture each aperture 46a, 46b, 46c to release the containers 22 held within the bands 34 of the carrier device 20. Each zip strip 24 is separated from the remainder of the respective container engaging portion 30, 32 by a separating structure 50.

[0026] At one end of each zip strip 24, a tab portion 50 is provided for a consumer to grasp the portion 50 to initiate tearing of the respective zip strip 24. The tab portion 50 clearly denotes to a consumer the starting end of the zip strip 24 and may include an aperture there-through through which a consumer can place a finger for tearing the zip strip 24.

[0027] The separating structure 50 includes perforation lines 54a, 54b, 54c, one of each which is associated with a respective aperture 46a, 46b, 46c in the respective container engaging portion 30, 32. In addition, the separating structure 50 includes elongated slits 56a, 56b and openings 58a, 58b as described herein.

[0028] The openings 58a, 58b are provided along the outer margin 38 of the respective container engaging portion 30, 32 midway between adjacent apertures. That is, opening 58a is provided between aperture 46a and aperture 46b; opening 58b is provided between

aperture 46b and aperture 46c. Each opening 58a, 58b is spaced from the outermost side edge 60 of the respective container engaging portion 30, 32. Each opening 58a, 58b is generally triangular in shape, with the elongated side 62 of the triangle being generally adjacent to the outer side edge 60 of the container engaging portion 30, 32. The openings 58a, 58b are formed in the container engaging portions 30, 32 by suitable known means.

[0029] Each elongated slit 56a, 56b is provided along the outer margin 38 of the container engaging portion 30, 32 between each opening and the respective perforation line. That is, slit 56a is between opening 46a and perforation line 54a; slit 56b is between opening 46b and perforation line 54b. Each elongated slit 56a, 56b is generally adjacent to and spaced from the outer side edge 60 of the respective container engaging portion 30, 32. In addition, the end of each slit 56a, 56b which is proximate to the respective opening 58a, 58b is separated from the respective opening 58a, 58b by a narrow web 64a, 64b of material. The slits 56a, 56b are formed in each container engaging portion 30, 32 by suitable known means.

[0030] The perforation lines 54a, 54b, 54c may be formed from a series of spaced dots or, alternatively, a series of spaced short lines. Each dot in each perforation line 54a, 54b, 54c is separated from each other by a continuous, uninterrupted portion of the carrier device 20. The perforation lines 54a, 54b, 54c do not significantly reduce package integrity while facilitating tearing of the zip strips 24 on each side of the carrier device 20. The perforation lines 54a, 54b, 54c are formed by suitable known means.

[0031] The perforation lines 54a, 54b which are associated with the first and second apertures 46a, 46b each have a first portion 66 which extends at a slight angle relative to the side edge 60 of the container engaging portion 30, 32 and a second portion 68 which extends from the end of the first portion 66 toward the respective aperture 46a, 46b and ends proximate to the respective aperture 46a, 46b. The first and second portions 66, 68 meet at junction 70. The second portion 68 is angled relative to the first portion 66.

[0032] The perforation line 54a which is associated with the first aperture 46a, i.e. the aperture 46a which is closest to the start of the zip strip 24, starts at an end 74 of the container engaging portion 30, 32. The perforation line 54b which is associated with the middle aperture 46b is positioned between the opening 58a and the slit 56b. The middle perforation line 54b starts proximate to the opening 46a. Each slit 56a, 56b is separated from the respective perforation line 54a, 54b by a continuous section 72a, 72b of carrier material which is frangible as described herein. The frangible section 72a, 72b is the width of carrier material which is between the respective perforation line 54a, 54b and the respective slit 56a, 56b.

[0033] The perforation line 54c proximate to the last

aperture 46c, i.e. the aperture 46c which is closest to the end of the zip strip 24, starts proximate to the opening 58b and angles toward the aperture 46c. The perforation line 54c ends proximate to the aperture 46c. A slit is not provided adjacent to the last perforation line 54c because the zip strip 24 is not designed to be completely torn away from the remainder of the carrier device 20. Instead, the strip 24, after being torn as described herein, is integrally joined with the remaining portion of the carrier device 20 at point 76. Therefore, when the strip 24 is torn along its separating structure 50, the strip 24 remains attached to the carrier device 20 at point 76 and does not separate into a distinct, discardable device. Of course, if desired, the separating structure 50 can be modified so that the zip strip 24 completely separates from the remainder of the carrier 20.

[0034] In addition, between the end of the last perforation line 54c and the last aperture 46c, a single slit 78 may be provided to aid in directing the tearing forces inwardly into the last aperture 46c when the strip 24 is torn to free the container 22 held therewithin. The slit 78 is generally parallel to the side edge 60 of the carrier device 20 and is spaced from the end of the perforation line 54c and from the aperture 46c by a continuous portion of the carrier device 20. The slit 78 is formed by suitable means. The slit 78 may be slightly angled relative to the perforation line 54c and may be provided in association with any of the perforation lines. Alternatively, a pair or more of staggered slits may be provided between the end of any of the perforation lines and the respective aperture. The slits can be parallel to or angled relative to the side edge of the carrier device. Of course, no slits may be provided such that the last perforation line is identical to the other perforation lines.

[0035] The separating structure 50 permits a consumer to tear the zip strip 24 to substantially separate the strip 24 from the remainder of the respective container engaging portion 30, 32. The zip strip 24 may be torn to release the containers 22 from the package 24 array one at a time so as to maintain the remainder of the containers 22 in the package array, or in rapid succession one after another. If the containers 22 are released one at a time, the remainder of the containers 22 are retained in the package array by the untorn portion of the zip strip 24 so as to not separate from each other. The ability of the consumer to rupture one aperture 46a, 46b, 46c at a time prevents the containers 22 from becoming dislodged uncontrollably when the consumer wants to open the package 26.

[0036] Attention is now directed to Figures 2 and 2a. To release the first container 22 from the carrier device 20, the consumer grasps the tab portion 52 of the zip strip 24 and pulls in the direction of the first perforation line 54a. The perforation line 54a ruptures to start to separate the zip strip 24 from the remainder of the container engaging portion 30, 32 and the tearing forces are directed inwardly into the aperture 46a to com-

pletely rupture the aperture 46a which releases the container 22 in that aperture 46a while retaining the remainder of the containers 22 in all other apertures 46b, 46c. After the aperture is ruptured, continued or subsequent pulling force acts on the zip strip 24 so the tension on the outer margin 38 of the container engaging portion 30, 32 causes the narrow frangible section 72a between the perforation line 54a and the slit 56a to rupture. During this tensioning, the slit 56a widens and provides the ability of the frangible section 72a to accept the high stresses and still rupture. In addition, the slit 56a allows the pulling force to be concentrated across the frangible section 72a. If the slit 56a were not there, or were not elongated as shown, there would be little ability of the frangible section 72a to rupture. Additionally, if the slit 56a were replaced with perforations, the same function is not achieved and the frangible section 72a does not rupture.

[0037] To release the second container 22 from the carrier device 20, the consumer continues to pull the zip strip 24 along the length of the carrier device 20. The zip strip 24 is separated from the remainder of the container engaging portion 30, 32 along the slit 56a. As the consumer continues to pull the zip strip 24, the narrow web 64a between the slit 56a and the opening 58a is ruptured by the tension. This separates the zip strip 24 from the remainder of the container engaging portion 30, 32 along the opening 58a. Thereafter, as the consumer continues to pull on the zip strip 24, the middle perforation line 54b is ruptured. The shape of the opening 58a aids in rupturing the start of the perforation line 54b by directing the tearing forces into the perforation line 54b. When the middle perforation line 54b ruptures, the tearing forces are directed inwardly into the middle aperture 46b to completely rupture the middle aperture 46b to release the container 22 in that aperture 46b while retaining the last container 22 in the last aperture 46c. As the pulling force is applied to the zip strip 24, the tension on the outer margin 38 of the container engaging portion 30, 32 causes the slit 56b to widen and the narrow frangible section 72b between the middle perforation line 54b and the middle slit 56b to rupture.

[0038] To rupture the last aperture 46c to release the container 22 held therewithin, the consumer continues to pull the zip strip 24 along the length of the carrier device 20. The zip strip 24 is separated from the remainder of the container engaging portion 30, 32 along the slit 56b. As the consumer continues to pull the zip strip 24, the narrow web 64b between the slit 56b and the opening 58b is ruptured and the zip strip 24 is separated from the remainder of the container engaging portion 30, 32 along the opening 58a. Thereafter, as the consumer continues to pull on the zip strip 24, the last perforation line 54c is ruptured. The shape of the opening 58b aids in rupturing the start of the perforation line 54c by directing the tearing forces into the perforation line 54c. When the last perforation line 54c ruptures, the tearing forces are directed inwardly into the last aper-

ture 46c to completely rupture the last aperture 46c and to release the container 22 held therein. The zip strip 24 remains attached to the remainder of the container engaging portion 30, 32 at point 76.

[0039] As shown in the drawings, the zip strips 24 both start at the same end of the carrier device 20. It is to be understood that the zip strips 24 may start at opposite ends of the carrier device 20.

[0040] In addition, more than one middle aperture 46b, along with its associated separating structure 50 as described herein, may be provided in the carrier device 20. For example, if the carrier device 20 includes two middle apertures, the opening, perforation line and slit which are provided for the middle aperture shown in the drawings, are repeated for the other middle aperture.

[0041] Alternatively, the carrier device 20 can be formed from a flat, planar blank which can include a side handle, such as the one disclosed in EP-A-0728674 which, however, constitutes a prior art in accordance with Article 54(3) EPC.

#### Claims

1. A carrier device (20) for carrying a plurality of containers comprising: at least one container engaging portion (30, 32) formed from a flexible material, said container engaging portion (30, 32) comprising bands (34) disposed in a row and defining apertures (46) therein, each said aperture (46) for holding a single container therein, said bands (34) having an outer margin portion (38) extending longitudinally of said row, and separating means (50) on said outer margin portion (38), said carrier device being characterised in that said separating means (50) comprises a perforation line (54) associated with each said aperture (46) and an elongated slit (56) between adjacent perforation lines (54), each said perforation line (54) directing tearing forces into the respective apertures (46), for separating a portion of said outer margin portion (38) from the remainder of outer margin portion (38), said separable outer margin portion defining a zip strip (24), said tearing forces being formed by pulling said zip strip (24) to separate said zip strip (24) from the remainder of the outer margin portion (38).
2. A carrier device according to claim 1, wherein each said slit (56) is separated from one of said perforation lines (54) by a narrow web (72) of material which can be ruptured when said zip strip (24) is pulled.
3. A carrier device according to claim 1 or 2, further including an opening (58) positioned between adjacent apertures (46) in said container engaging portion and along said outer margin, each said opening

- (58) being positioned between one of said slits (56) and one of said perforation lines (54) and separated from each of said slit (56) and said perforation (54) by a narrow section of material (64) which can be ruptured when said zip strip (24) is pulled.
4. A carrier device according to any one of the preceding claims, further including two container engaging portions (30, 32).
  5. A carrier device according to any one of the preceding claims, further including a handle portion (48) connected to said container engaging portion (30, 32).
  6. A carrier device according to claim 4 or 5, further including two of said container engaging portions (30, 32), and a handle portion (48) connected to adjacent inner margins (36) of said container engaging portions (30, 32), and wherein each of said container engaging portions (30, 32) includes said bands (40) at opposite ends of the respective container engaging portion (30, 32) and at least one intermediate band (42).
  7. A carrier device according to any one of the preceding claims, wherein said perforation lines (54) comprise a first portion (66) and a second portion (68), each said first portion (66) extending generally parallel to a side edge (60) of said outer margin and each said second portion (68) extending from an end of said first portion (66) and inwardly towards the respective aperture (46).
  8. A package comprising a plurality of containers (22) and a carrier (20) in accordance with any one of the preceding claims, each container (22) being located in its respective aperture (46) of the carrier and being held in place by the bands (34).
- Patentansprüche**
1. Vorrichtung (20) zum Tragen einer Anzahl von Behältern mit: mindestens einem Behälter in Eingriff nehmenden Abschnitt (30, 32), der aus einem flexiblen Material gebildet ist, wobei der Behälter in Eingriff nehmende Abschnitt (30, 32) Bänder (34) aufweist, die in einer Reihe angeordnet sind und Öffnungen (46) in sich umgrenzen, wobei jede Öffnung (46) zum Halten eines einzelnen Behälters in sich vorgesehen sind, und wobei Bänder (34) einen äußeren Begrenzungsabschnitt (38) aufweisen, der sich längs der Reihe erstreckt, sowie Separierungsmittel (50) auf dem äußeren Begrenzungsbereich (38), wobei die Trägervorrichtung dadurch gekennzeichnet ist, daß das Separierungsmittel (50) assoziiert mit jeder Öffnung (46) eine Perforationslinie (54) aufweist sowie einen länglichen Schlitz (56) zwischen benachbarten Perforationslinien (54), wobei jede Perforationslinie (54) Reißkräfte in die jeweiligen Öffnungen richtet, und zwar zum Separieren eines Abschnitts des äußeren Begrenzungsabschnitts (38) vom übrig bleibenden äußeren Begrenzungsabschnitt (38), wobei der separierbare äußere Begrenzungsabschnitt einen Reißstreifen (24) begrenzt, und wobei die Reißkräfte durch Ziehen des Reißstreifens (24) zum Separieren des Reißstreifens (24) vom übrig bleibenden äußeren Begrenzungsabschnitt (38) gebildet sind.
  2. Trägervorrichtung nach Anspruch 1, wobei jeder Schlitz (56) von einer der Perforationslinien (54) durch einen schmalen Steg (72) aus Material separiert ist, welcher zerrissen werden kann, wenn der Reißstreifen (24) gezogen wird.
  3. Trägervorrichtung nach Anspruch 1 oder 2 zusätzlich mit einer Öffnung (58), welche zwischen benachbarten Öffnungen (46) in dem Behälter in Eingriff nehmenden Abschnitt und entlang der äußeren Begrenzung angeordnet ist, wobei die Öffnung (58) zwischen einem der Schlitze (56) und einer der Perforationslinien (54) angeordnet und von jedem der Schlitze (56) und der Perforationen (54) durch einen schmalen Materialbereich (64) getrennt ist, welcher zerstört werden kann, wenn der Reißstreifen (24) gezogen ist.
  4. Trägervorrichtung nach einem der vorhergehenden Ansprüche, zusätzlich mit zwei Behälter in Eingriff nehmenden Abschnitten (30, 32).
  5. Trägervorrichtung nach einem der vorhergehenden Ansprüche zusätzlich mit einem Griffabschnitt (48), welcher mit dem Behälter in Eingriff nehmenden Bereich (30, 32) verbunden ist.
  6. Trägervorrichtung nach Anspruch 4 oder 5 zusätzlich mit zwei Behälter in Eingriff nehmenden Abschnitten (30, 32) und einem Griffabschnitt (48), der zu benachbarten inneren Begrenzungen (36) der Behälter in Eingriff nehmenden Bereiche (30, 32) verbunden ist, und wobei jeder der Behälter in Eingriff nehmenden Abschnitte (30, 32) die Bänder (40) an gegenüberliegenden Enden des jeweiligen Behälter in Eingriff nehmenden Abschnitts (30, 32) und an mindestens einem mittleren Band (42) umfaßt.
  7. Trägervorrichtung nach einem der vorhergehenden Ansprüche, wobei die Perforationslinien (54) einen ersten Abschnitt (66) und einen zweiten Abschnitt (68) umfassen, wobei jeder erste Abschnitt (66) sich im wesentlichen parallel zu einer Seitenkante (60) der äußeren Begrenzung und jeder zweite Abschnitt (68) von einem Ende des ersten

Abschnitts (66) und einwärts zur jeweiligen Öffnung (46) erstreckt.

8. Packung mit einer Anzahl von Behältern (22) und einem Träger (20) nach einem der vorhergehenden Ansprüche, wobei jeder Behälter (22) in seiner jeweiligen Öffnung (46) des Trägers angeordnet ist und durch die Bänder (34) am Ort gehalten ist.

#### Revendications

1. Dispositif de support (20) pour porter plusieurs récipients, comprenant : au moins une partie (30, 32) s'appliquant contre les récipients et formée d'une matière souple, ladite partie (30, 32) s'appliquant contre les récipients comprenant des bandes (34) disposées en une rangée et délimitant des ouvertures (46) dans cette dernière, chacune desdites ouvertures (46) étant destinée à tenir intérieurement un unique récipient, lesdites bandes (34) ayant une partie de bord extérieur (38) orientée dans la direction de la longueur de ladite rangée et un moyen de séparation (50) situé sur ladite partie de bord extérieur (38), ledit dispositif de support étant caractérisé en ce que ledit moyen de séparation (50) comprend une ligne de perforations (54) associée à chacune desdites ouvertures (46) et une fente allongée (56) située entre des lignes voisines de perforations (54), chacune desdites lignes de perforations (54) dirigeant des forces de déchirure dans les ouvertures respectives (46) afin de séparer une partie de ladite partie de bord extérieur (38) du reste de la partie de bord extérieur (38), ladite partie séparable de bord extérieur constituant un ruban de déchirure (24), lesdites forces de déchirure s'exerçant en tirant ledit ruban de déchirure (24) afin de séparer ledit ruban de déchirure (24) du reste de la partie de bord extérieur (38).

2. Dispositif de support selon la revendication 1, dans lequel chacune desdites fentes (56) est séparée de l'une desdites lignes de perforations (54) par une lanière étroite (72) de matière qui peut être déchirée lorsque ledit ruban de déchirure (24) est tiré.

3. Dispositif de support selon la revendication 1 ou 2, comprenant par ailleurs un trou (58) placé entre ouvertures voisines (46) dans ladite partie s'appliquant contre les récipients et le long dudit bord extérieur, chacun desdits trous (58) étant positionné entre l'une desdites fentes (56) et l'une desdites lignes de perforations (54) et étant séparé de chacune desdites fentes (56) et desdites perforations (54) par une section étroite de matière (64) qui peut être déchirée lorsque ledit ruban de déchirure (24) est tiré.

4. Dispositif de support selon l'une quelconque des

revendications précédentes, comprenant par ailleurs deux parties (30, 32) s'appliquant contre les récipients.

5. Dispositif de support selon l'une quelconque des revendications précédentes, comprenant par ailleurs une partie de poignée (48) raccordée à ladite partie (30, 32) s'appliquant contre les récipients.

6. Dispositif de support selon la revendication 4 ou 5, comprenant par ailleurs deux desdites parties (30, 32) s'appliquant contre les récipients et une partie de poignée (48) raccordée à des bords intérieurs voisins (36) desdites parties (30, 32) s'appliquant contre les récipients, et dans lequel chacune desdites parties (30, 32) s'appliquant contre les récipients comprend lesdites bandes (40) situées aux extrémités opposées de la partie respective (30, 32) s'appliquant contre les récipients et au moins une bande intermédiaire (42).

7. Dispositif de support selon l'une quelconque des revendications précédentes, dans lequel lesdites lignes de perforation (54) comprennent une première partie (66) et une seconde partie (68), chacune desdites premières parties (66) étant globalement parallèle à une lisière latérale (60) dudit bord extérieur et chacune desdites secondes parties (68) allant d'une extrémité de ladite première partie (66) vers l'intérieur et vers l'ouverture respective (46).

8. Emballage comprenant plusieurs récipients (22) et un support (20) selon l'une quelconque des revendications précédentes, chaque récipient (22) étant placé dans son ouverture respective (46) du support et étant maintenu en place par les bandes (34).

FIG. 1





